

IAL3SK1 (F)

Termination set in shrinking technology for use in non-hazardous area.



Termination Set non-Ex



- Compact design
- Temperature resistant up to 130°C (IAL3SK1 F 120°C)
- Quick and easy to assemble
- Applicable for different heating tapes CLD; ILLw; ILM, ILMw; ILH (up to 120°C); ILHS...CF
- Different sets separately available

Description

The IAL3SK1 is a termination set which is easy and fast to assemble.

The heating tape will be connected with the feeding cable by using a ceramic terminal block and afterwards over shrunk with a special shrink tubing.

Because of the illustrated instruction manual the installation is very easy and requires no special tools.



Technical Data

Max. Ambient Temperature:	+130°C or +120°C for IAL3SK1 F
Heating Tapes:	CLD, ILL, ILLw, ILM, ILMw, ILH
Cross Section:	up to 2.5mm ²
Length Connection Side:	120mm
Length End Seal:	58mm

Further Information

Please consult the installation instructions!

Ordering Information

Part number:	
IAL3SK1:	Power connection and end seal in one kit, for heating tapes with polyolefin outerjacket
IAL3SK1 F:	Power connection and end seal in one kit, for heating tapes with fluoropolymer outerjacket

Alternative Products

Part number:	
IAL5SS:	Non-Ex Termination set in screw technology

Additional Products

Part number:	
IAL3VK1:	Connection set (Heating tape – Heating tape)
IAL3AG1:	Power connection and end seal for direct entry in a special enclosure
AG 101:	Non-Ex glass fiber reinforced Polyester enclosure for 1-3 heating circuits