



PRODUCT SPECIFICATIONS

TubeTrace® Type SI/MI

“LIGHT” STEAM TRACED INSTRUMENT TUBING

APPLICATION

Freeze protection or process temperature maintenance with a tube temperature range: 5°C to 121°C. Designed to provide freeze protection or temperature maintenance for metallic and non-metallic tubing with “light” steam trace, TubeTrace Type SI/MI is suitable for use with process analyzers, emissions analyzers, and impulse lines to flow or pressure transmitters where steam or hot liquid is the preferred heating media.

TubeTrace Type SI/MI “light” steam trace is a metallic tracer tube that is isolated from direct contact with the process tube(s). The tracer tube and process tube(s) benefit from consistent heat transfer and performance along the entire length of the bundle.

Unlike field fabricated and insulated tubing, TubeTrace engineered pre-insulated tubing provides superior weather proofing and long term reliability.

RATINGS

SI and MI “Light” Trace	Ratings
Available Tracer Tube Diameters	1/4”, 3/8” and 1/2”
Available Tracer Tube Materials	Copper and Stainless Steel
Typical Process Tube Temperature	5°C to 121°C
Maximum Steam Temperature*	205°C/1690 kPa
Typical Temperature Difference Tracer Tube vs. Process Tube	More Than 55°C ⁴


HOW TO SPECIFY

SI - 4F1-3B1 - ATP - 035 / 035

<p>TubeTrace Type</p> <p>SI = Single Tube MI = Multiple Tubes</p>	<p>Process Tube(s) O.D.</p> <p>1 = 1/8" 2 = 1/4" 3 = 3/8" 4 = 1/2" 5 = 5/8" 6 = 3/4"</p>	<p>Process Tube(s) Material</p> <p>A = 316 SS Welded C = PFA Teflon¹ D = Monel² E = Titanium F = 316 SS Seamless G = 304 SS Welded H = 304 SS Seamless J = Alloy C276 K = Alloy 825 L = Alloy 20 M = FEP Teflon T = TFE Teflon X = Special</p>	<p>Number of Process Tube(s)</p> <p>1 2 3</p>	<p>Tracer Tube O.D.</p> <p>2 = 1/4" 3 = 3/8" 4 = 1/2"</p>	<p>Tracer Tube Material</p> <p>A = 316 SS Welded B = 122 Copper F = 316 SS Seamless</p>	<p>Bundle Jacket</p> <p>ATP³ TPU</p>	<p>Number of Tracer Tube(s)</p> <p>1</p>	<p>Process Tube(s) Wall Thickness</p> <p>028 = .028" (SS Only) 035 = .035" 040 = .040" (Plastic Only) 047 = .047" (Plastic Only) 049 = .049" 062 = .062" (Plastic Only) 065 = .065" 083 = .083" (SS Only)</p>	<p>Tracer Tube(s) Wall Thickness</p> <p>032 = .032" 035 = .035" 049 = .049" 065 = .065"</p>
--	---	---	--	--	--	--	---	--	--

Notes . . .

- Teflon is a trademark of E. I. duPont de Nemours Co., Inc.
- Monel is a trademark of Inco Alloys International, Inc.
- Black ATP is standard; other jacket materials are available.
- Please contact factory for performance data when using for critical temperature applications.



CONSTRUCTION

- 1 Process tube(s)
- 2 Heat reflective tape
- 3 Tracer tube [isolated from process tube(s)]
- 4 Non-hygroscopic glass fiber insulation
- 5 Polymer outer jacket

PRODUCT FEATURES

- Consistent heat transfer and thermal performance
- Superior weather proofing
- Long coils minimize waste

Note

* If bundle jacket is to remain below 140°F (60°C) in +80°F (27°C) ambient (in consideration of personnel burn risk) tube temperature must remain below 400°F (205°C). Alternative designs to keep jacket below 140°F (60°C) in higher ambients and/or with higher tube temperatures are available. Contact TC-E.