


Datasheet	Pallet heating box	Tmax 65°C
-----------	--------------------	-----------

Features and benefits
<ul style="list-style-type: none"> • Suitable for chemical-technical products in a wide range of container sizes • Self-safe PTC heating element (Tmax 65°C): Prevents uncontrolled heating in the event of a fault • Electronic temperature controller, easily adjustable via three buttons • Can be moved using a pallet and a manual pallet lift or two people • Silicone-free • EPP housing: Energy-efficient and impact-resistant

Technical data	HBC65-V244-230V-R	
	Operating voltage	230 VAC
	Rated power	600 W (@10°C)
	Protection class	I (protective earth)
	IP protection class	IP30
	Housing	EPP
	Weight	23,1 kg
	Connection cable (enclosed) with type F plug	1,5 m
	External dimensions (LxWxH) Inner dimensions (LxWxH)	1200 x 800 x 540 mm 1120 x 660 x 370 mm

Description
<p>The optimum solution for the efficient preheating of chemical-technical products in a wide range of container sizes. This heating box makes it possible to heat larger storage quantities to operating temperature in a targeted and energy-efficient manner without having to heat the entire warehouse.</p> <p>The flexible adaptation to different packaging sizes, the targeted heating of only the required products and the high efficiency make our heating box the sustainable choice for storage in winter.</p>