

## ACCESSORIES

### LAB-EX-XTV-KTV

Aluminum tag plate for XTV and KTV self-regulating heating cables. To be installed if T-class compliance was proven by stabilized design and not by unconditional T-rating.  
PN: 1244-011961      Weight: 0.04 kg

### LAB-EX-FXT

Aluminum tag plate. To be installed when parallel constant wattage FMT or FHT heating cables are used in hazardous areas.  
PN: 1244-006953      Weight: 0.04 kg

### PI-LABEL-EX


Aluminum tag plate. To be installed when series polymer insulated XPI & XPI-S heating cables are used in hazardous areas.  
PN: 1244-006940      Weight: 0.04 kg

### PI-LABEL-NH

Aluminum tag plate. To be installed when series polymer insulated XPI & XPI-S heating cables are used non hazardous areas. This label is not mandatory but highly recommended for future reference.  
PN: 1244-006941      Weight: 0.04 kg


## PIPE STRAPS

Metal straps for pipe mounting of integrated power connections, above the insulation tees and end seals as well as support brackets and the tubular insulation entry.  
Banding: stainless steel



Pipe outer diameter in mm	(inches)	Pipe strap	PN (Weight)
20 - 47	(1/2" - 11/4")	PSE-047	700333-000 (0.017 kg)
40 - 90	(1 1/4" - 3")	PSE-090	976935-000 (0.024 kg)
60 - 288	(2" - 10")	PSE-280	664775-000 (0.052 kg)
60 - 540	(2" - 20")	PSE-540	364489-000 (0.052 kg)

## PROTECTIVE GROMMET




### G-02

Silicone grommet that protects the heating cable at sharp edges such as endplates of insulation cladding, flanges etc. It can be cut-to-length and resists temperatures up to 215°C.  
Sold in pieces of 1 m.

PN: 412549-000      Weight: 0.37 kg/m

## FIXING MATERIALS

Self-adhesive tape for fixing the heating cables on pipes or other equipment.



### GT-66

Glass cloth tape for attaching heating cable to pipe.  
Not for stainless steel pipes or for installation temperatures below 5°C.  
20 m per roll, 12 mm width.  
PN: C77220-000      Weight: 0.053 kg

### GS-54

Glass cloth tape for attaching heating cable to pipe.  
For stainless steel pipes or for any installation below 5°C.  
16.5 m per roll, 12 mm width.  
PN: C77221-000      Weight: 0.048 kg



[WWW.PENTAIRTHERMAL.COM](http://WWW.PENTAIRTHERMAL.COM)

**EUROPE, MIDDLE EAST, AFRICA**

Tel: +32.16.213.511  
Fax: +32.16.213.603  
[thermal.info@pentair.com](mailto:thermal.info@pentair.com)

**UNITED KINGDOM**

Tel: 0800 969 013  
Fax: 0800 968 6241  
[salesthermaluk@pentair.com](mailto:salesthermaluk@pentair.com)

**IRELAND**

Tel: 1800 654 241  
Fax: 1800 654 240  
[salesie@pentair.com](mailto:salesie@pentair.com)

Pentair is owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

© 1998-2016 Pentair.